

*Easy-To-Use Homeowners Plow
with Super Slick Corrosion Free Poly
Moldboard*



SNO-PRO HOME-PRO Sno-Pro Home-Pro Light Weight Poly

- Hitch-n-Run® System, fastest attachment and detachment.
- Specifically built for compact and light duty trucks.
- Hide-Away Hydraulics, cavity tucks away hydraulic power system.
- Hydraulic Jack Stand, this patented device utilizes hydraulics to position the plow at the exact height required for reattachment.
- Full Trip Design, built to withstand season after season of hard use.
- World Class Fit and Finish, light weight poly.
- Hide-Away Mount, clean and professional describes our remaining receiver frame when the plow is removed.
- High visibility low profile halogen headlamps with park/turn signal lights.

*The Original
The Best!*



SNO-PRO 3000 FULL-TRIP Sno-Pro Full-Trip All Steel Features

- Hitch-n-Run® System, fastest attachment and detachment.
- Hide-Away Hydraulics, cavity tucks away hydraulic power system.
- Hydraulic Jack Stand, this patented device utilizes hydraulics to position the plow at the exact height required for reattachment.
- Extended Push Frame, widest on the market, measures 4-feet end-to-end.
- Full Trip Design, built to withstand season after season of hard use.
- Aggressive attack angle provides better scraping ability.
- Center punched cutting edge extends life, just flip to new clean edge.
- Hide-Away Mount, clean and professional describes our remaining receiver frame when the plow is removed.
- High visibility low profile halogen headlamps with park/turn signal lights.

*Heavy-Duty
Contractor Plow
with Super Slick
Corrosion Free
Moldboard*



SNO-PRO 3000 FULL-TRIP POLY Sno-Pro Full-Trip Poly Features

- Hitch-n-Run® System, fastest attachment and detachment.
- Hide-Away Hydraulics, cavity tucks away hydraulic power system.
- Hydraulic Jack Stand, this patented device utilizes hydraulics to position the plow at the exact height required for reattachment.
- Extended Push Frame, widest on the market, measures 4-feet end-to-end.
- Full Trip Design, built to withstand season after season of hard use.
- Slick polymer surface allows faster and easier snow removal.
- Center punched cutting edge extends life, just flip to new clean edge.
- Hide-Away Mount, clean and professional describes our remaining receiver frame when the plow is removed.
- High visibility low profile halogen headlamps with park/turn signal lights.



SNO-PRO HOME-PRO

Sno-Pro Home-Pro Features

SPECIFICATION	7'	7-1/2'
Blade Width (straight)	84"	90"
Plowing Width (full angle)	74"	79.5"
Blade Height	24"	26"
Blade Skin Thickness	3/16" Poly	3/16" Poly
Cutting Edge	1" x 6" Poly Reversible	1" x 6" Poly Reversible
Cutting Edge Attack Angle	18°	18°
Vertical Ribs	5	5
Trip Springs	2	2
Angle Cylinders	1.5" x 10"	1.5" x 10"
Lift Cylinder	1.5" x 7.5"	1.5" x 7.5"
Skid Shoes - Cast Iron	N/A	N/A
Sector	45°	45°
Attachment System	HITCH-N-RUN SYSTEM™ <i>Worlds Fastest Attachment Snowplow</i>	
Jack System	Switch Activated Hydraulic	Switch Activated Hydraulic
Average Weight	430 lbs.	450 lbs.

SNO-PRO 3000 FULL-TRIP

Sno-Pro Full-Trip All Steel Features



SPECIFICATION	7-1/2'	8'	9'
Blade Width (straight)	90"	96"	108"
Plowing Width (full angle)	79.5"	85"	95"
Blade Height	28"	28"	28"
Blade Skin Thickness	11 Ga	11 Ga	11 Ga
Cutting Edge	3/8" x 6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	1/2" x 6" High Carbon Reversible
Cutting Edge Attack Angle	18°	18°	18°
Vertical Ribs	6	6	6
Trip Springs	4	4	4
Angle Cylinders	1.5" x 10"	1.5" x 10"	1.5" x 10"
Lift Cylinder	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"
Skid Shoes - Cast Iron	2	2	2
Sector	54°	54°	54°
Attachment System	HITCH-N-RUN SYSTEM™ <i>Worlds Fastest Attachment Snowplow</i>		
Jack System	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic
Average Weight	685 lbs.	740 lbs.	820 lbs.

SNO-PRO 3000 FULL-TRIP POLY

Sno-Pro Full-Trip Poly Features



SPECIFICATION	7-1/2'	8'
Blade Width (straight)	90"	96"
Plowing Width (full angle)	79.5"	85"
Blade Height	28"	28"
Blade Skin Thickness	3/8" Poly	3/8" Poly
Cutting Edge	3/8" x 6" High Poly Reversible	3/8" x 6" High Poly Reversible
Cutting Edge Attack Angle	18°	18°
Vertical Ribs	6	8
Trip Springs	4	4
Angle Cylinders	1.5" x 10"	1.5" x 10"
Lift Cylinder	1.5" x 7.5"	1.5" x 7.5"
Skid Shoes - Cast Iron	2	2
Sector	54°	54°
Attachment System	HITCH-N-RUN SYSTEM™ <i>Worlds Fastest Attachment Snowplow</i>	
Jack System	Switch Activated Hydraulic	Switch Activated Hydraulic
Average Weight	675 lbs.	750 lbs.